

can-am

OUTLANDER 6X6 XU+ 450 T

2022

HIGHLIGHTS

- Rotax® single cylinder engine
- Continuously Variable Transmission (CVT) with extra low L-gear
- 3,500-lb (1,588 kg) winch
- Speed limiter
- Heavy-Duty front bumper
- 26-in. (66 cm) Carlisle ACT HD 6-ply tires
- 12-in. (30.5 cm) cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Heated grips & throttle
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Quick release sway bar
- Double A-arm front suspension
- Relocated air intakes
- RF Digitally Encoded Security System (D.E.S.S.™)
- 2.9-gal (10.9 L) water-resistant rear compartment
- Cargo extenders
- 159 kg capacity rear bed with cargo extenders



Tundra Green

ENGINE

Type	28 kW (38 hp), Rotax® 427 cc single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTc™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok† QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 8.8 in. (22 cm) travel
Rear Shocks	Oil

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. (30.5 cm) cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	443 kg
L x W x H	279 x 118.8 x 124 cm
Wheelbase	208 cm
Ground Clearance	26.7 cm
Seat Height	85.8 cm
Rack Capacity	Front: 54 kg / Rear: 159 kg
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	907 kg trailer with brakes 465 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES

Gauge	4.5 in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	70 W from dual 35-W front light and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-Duty front bumper, Central skid plate, heated grips

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved.™, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

